



SIZES



PACKING



60 Pairs / carton
5 Pairs / bag



Cat.2

3144

413X4X

EN-388 - Mechanical risk

Abrasion	Cut	Tear	Perforation
3	1	4	4

EN-407 - Thermal risk

Flammability	4
Contact heat	1
Convective heat	3
Radiant heat	X
Small splashes of molten metal	4
Large splashes of molten metal	X

TECHNIQUE DESCRIPTION

- Red cowsplit leather.
- Flannel lining.
- Thickness: 1,1-1,3 mm.
- Length: 34 cm.

RECOMMENDED USES

- Steel framework, boiler works
- Maintenance
- Assembly
- MIG welding

Size	Weight	Capacity (cm)	EAN code
U	20.50 kg	90x35x22	8428371007718

OUTSTANDING FEATURES

- Split leather: this is the inner side of the leather. DERMIS. Excellent mechanical properties.
- Breathable.
- Good heat and perforation resistance .
- Split cuff that provides protection to the forearm.
- Flannel lining for better protection against high temperatures.
- A type: good for MIG welding.
- Less dexterity.

"The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary."